

LumaSoft Series

Direct/Indirect LED Troffers



DesignLights Consortium™ Qualified Luminaires:
L622CL27U4K



L614C

L622C

Housing:

Direct/Indirect Formed Cold Rolled Steel Housing. Post-Painted with Flat White Polyester Powdercoat Finish Over a Nanoceramic Treatment to Provide Enhanced Corrosion Resistance and Better Paint Adhesion. Includes Built-in Earthquake Brackets. Low Profile for Shallow Plenum Spaces.

Diffuser:

Translucent Acrylic Diffuser for Even Light Distribution and Less Glare.

Mounting:

Mounts on Inverted T-Bar Grid Ceilings.

LEDs:

Luminous Flux: 2700 Nominal Lumens
CRI: 80, CCT: 4000K
Operating Temperature: 0 - 40°C
50,000 Hours

Wattage:

LED: 1 x 4, 2 x 2: 28w

Driver:

Electronic Driver, 120-277V, 50/60Hz

Listing & Ratings:

CSA: Listed for Dry Locations

LM-79 Report Available on Select Models.

Flex Whip Sold Separately.

LumaSoft Direct/Indirect LED Troffers

Catalog #

Description


Complete Units

Ordering Information


Example: L622CL27U4KSFD1

L6	Model:	L6=Recessed Mount
22	Size:	14=1'x4', 22=2'x2'
C	Diffuser:	C=Translucent Acrylic Diffuser
L	LED Mfr:	L=LG Innotek
27	Lumens	27=2700 Nominal Lumens
U	Driver:	U=120-277V
4K	Color Temp:	4K=4000K
SF	Options:	D3=0-10V Dimming SF=Single Fuse, S1=20K Surge Protector


DIMENSIONS



L622: 24"
L614: 48"



L614



L622

KELSEY-KANE LIGHTING MFG. CO.

Voice & Text: 954-772-3187 / E-Mail: info@kelsey-kane.com / Website: www.kelsey-kane.com

KELSEY-KANE LIGHTING MFG. CO.

Voice & Text: 954-772-3187

E-Mail: info@kelsey-kane.com

Website: www.kelsey-kane.com

Catalog #	Description
U6F38FMC183S9	6' 3/8" FMC Flex Whip, 18/3, Straight and 90° Connectors
ACRINS4	One 4' Insert for Acrylic Diffusers, Further Softens LED. Order One Piece for 1'x4'
ACRINS2	One 2' Insert for Acrylic Diffusers, Further Softens LED. Order Two Pieces for 2'x2'.

LumaSoft Series

Direct/Indirect LED Troffers



U6F38FMC183S9