



# AmberLED LEDicated Vaporproof-Straight Shade


**L70**  
 25°C **187,000 Hours**



**VB53Q**

### Dimensions

**Diameter (D)** 16" (408mm)  
**Height (A)** **VP53Q** 12 3/4" (326mm)  
**VB53Q** 12" (305mm)



### Order Information Example:

**VP53QF1X23UAMPSFSS**

	<b>F</b>	<b>1X23</b>	<b>U</b>	<b>AM</b>			<b>SS</b>
<b>Model</b>	<b>Optics</b>	<b>Wattage</b>	<b>Driver</b>	<b>CCT</b>	<b>Color</b>	<b>Options</b>	<b>Shield</b>

**VB53Q**=AmberLED LEDicated Box Mount Vaporproof  
**VP53Q**=AmberLED LEDicated Pendant Mount Vaporproof

**F**=Type V

**1X23**=23w

**U**=120-277V

**AM**=Amber

**P**=Platinum  
**C**=Custom  
 (Consult Factory)

**SF**=Single Fuse  
**DF**=Double Fuse

**SS**=Straight Shade

### Project Information:

Project Name: \_\_\_\_\_ Fixture Type: \_\_\_\_\_  
 Complete Catalog #: \_\_\_\_\_ Date: \_\_\_\_\_  
 Comments: \_\_\_\_\_

### Certification & Listings:



TURTLE-SAFE

Certification #2018-001

Specifications subject to change without notice. Rev. 041718

AmberLED LEDicated Vaporproof pendant and ceiling mount fixtures with straight shades are available with a shielded IES Type V distribution, and are certified by the Florida Fish & Wildlife Conservation Commission (FWC) for wildlife applications that are directly visible from the shore requiring monochromatic AMBER light. LEDs operate between 585 and 595 nm, greater than 560nm required by FWC. Typical applications include retail centers, hotels, residential, parks, schools and universities, office buildings and medical facilities. Mounting heights of up to 12 feet can be used based on light level and uniformity requirements.

### Specifications and Features:

#### Housing:

Heavy Duty Die Cast Aluminum Housing with Integral Heat Sinking, 3/4" NPS Threaded Mounts. Includes Shade Required to Maintain FWC Certification.

#### Listing & Ratings:

CSA: Listed for Wet Locations, ANSI/UL 1598, 8750  
 IP66 Sealed LED Compartment

#### Finish:

Smooth Powdercoat Finish Over a Chromate Conversion Coating. Custom Colors Available Upon Request.

#### Lens:

Flat Clear Tempered Glass Lens

#### Mounting Options:

Pendant Mount or Surface Mount on Ceiling.

#### AmberLED:

Aluminum Boards

#### Wattage:

Array: 22w, System: 27w  
 (175w HID Equivalent)

#### Driver:

Electronic Driver, 120-277V, 50/60Hz; Dimmable Driver

#### Warranty:

5-Year Warranty for -40°C to +50°C Environment.

See Page 2 for Projected Lumen Maintenance Table.

# AmberLED

# AmberLED LEDicated Vaporproof-Straight Shade

L70  
 25°C

187,000 Hours

## Accessories & Replacement Parts:



**VS30S**    **VWGS\***    **CPRB**    **CPRB1**  
**CPRC1**    **CPRB3**    **CPSPR**    **CPSPS**


\*Shown Mounted

Accessories (Order separately, Field installed)	
VS30S	Straight Aluminum Shade, Repaintable Textured Gray Finish. Not for use with VW43.
VWGS	Wire Guard for Straight Shade, Stainless Steel
CPRB	Reducer Bushing, ¼" to ½", use with Swivel Mount
CPRB1	Die Cast Round Electrical Box with Five (5) ½" Coin Plugs
CPRC1	Backplate, ½" Coin Plugs
CPRB3	Die Cast Round Electrical Box with Five (5) ¼" Coin Plugs

Mounting Accessories (Order separately, Field installed)	
CPSPR	Swivel Pendant Mount - Round, for Angled or Straight Ceilings, Fits ¼" Conduit, Includes Reducer Bushing (to ½") & Set Screw, Powdercoat Finish
CPSPS	Swivel Pendant Mount - Square, or Angled or Straight Ceilings, Fits ¼" Conduit; Includes Reducer Bushing (to ½") & Set Screw, Powdercoat Finish

## Photometric Data

### Amber LED - Spectral Chart



## Photometric Performance

LED Board Watts	Drive Current (mA)	Input Watts	Optics
AmberLED 23w	116	27	Type V

## Projected Lumen Maintenance

Data shown for Amber LEDs			Compare to MH				
TM-21-11	Input Watts	Initial	25,000 Hrs	50,000 Hrs	100,000 Hrs	Calculated L70@ 25°C	
L70 Lumen Maintenance @ 25°C / 77°F	27	1.00	0.96	0.92	0.84	187,000	
TM-21-11	Input Watts	Initial	25,000 Hrs	50,000 Hrs	100,000 Hrs	Calculated L70@ 50°C	
L70 Lumen Maintenance @ 50°C / 122°F	27	1.00	0.93	0.86	0.72	107,000	
TM-21-11	Input Watts	Initial	25,000 Hrs	50,000 Hrs	100,000 Hrs	Calculated L80@ 40°C	
L80 Lumen Maintenance @ 40°C / 104°F	27	1.00	0.94	0.88	0.76	82,000	

**NOTES:**

1. Projected per IESNA TM-21-11. Data references the extrapolated performance projections for the 116mA base model in a 25°C ambient, based on 10,000 hours of LED testing per IESNA LM-80-08.
2. Compare to MH box indicates suggested Light Loss Factor (LLF) to be used when comparing to Metal Halide (MH) systems.