

## EasyLED Series

### Reveal Round Sconce



WBB3Q

#### Housing:

Die Cast Aluminum Housing with Flush Mount Easy-Hang Wall Bracket, Built-In Level, Flat Top, Powdercoat Finish Over a Chromate Conversion Coating, Sealed Driver Compartment. Photocell Adaptable.

#### Lens:

Clear Inner Lens to Seal LED Array.

#### Mounting:

Mount Over a 4" Recessed Outlet Box

#### LumaFit LED:

Delivered Lumens: 1,539 (Clear Array Lens)

CRI: 80+

CCT: 4000K

Rated Life: 50,000 Hours

5-Year Warranty

Aluminum Boards

#### Wattage:

Array: 16.6w, System: 19.7w

#### Driver:

Electronic Driver, 120-277V, 50/60Hz

Dimmable Driver

#### Listings & Ratings:

IP67

Operating Temperatures: -20°C to +40°C

#### Options:

Surge Protection

Custom Colors Available Upon Request.

### Reveal Round Sconce

#### Catalog #

#### Description

#### Complete Units

#### Ordering Information

Example: WBB3QF1X16U4KCZSP

WBB3	Model:	WBB3
Q	LED Mfr:	Q=QSSI
F	Optics:	F=Medium Beam Spread
1X	Number of Arrays:	1X=One
16	Wattage:	16=16w
U	Ballast:	U=120-277V
4K	CCT:	4K=4000K
C	Lens:	C=Clear Array Lens
Z	Color:	Z=Bronze, B=Black
SP	Options:	SF=Single Fuse, DF=Double Fuse, SP=Surge Protection

**KELSEY-KANE LIGHTING MFG. CO.**

Voice & Text: 954-772-3187

E-Mail: [info@kelsey-kane.com](mailto:info@kelsey-kane.com)

Website: [www.kelsey-kane.com](http://www.kelsey-kane.com)