

EasyLED Series

Reveal Square Sconce



WBB4Q

Housing:

Die Cast Aluminum Housing with Flush Mount Easy-Hang Wall Bracket, Built-In Level, Flat Top, Powdercoat Finish Over a Chromate Conversion Coating, Sealed Driver Compartment. Photocell Adaptable.

Lens:

Clear Inner Lens to Seal LED Array.

Mounting:

Mount Over a 4" Recessed Outlet Box

LumaFit LED:

Delivered Lumens: 1,611 (Clear Array Lens)

CRI: 80+

CCT: 4000K

Rated Life: 50,000 Hours

5-Year Warranty

Aluminum Boards

Wattage:

Array: 16.6w, System: 19.7w

Driver:

Electronic Driver, 120-277V, 50/60Hz

Dimmable Driver

Listings & Ratings:

IP67

Operating Temperatures: -20°C to +40°C

Options:

Surge Protection

Custom Colors Available Upon Request.

Reveal Square Sconce

Catalog

Description

Complete Units

Ordering Information

Example: WBB4QF1X16U4KCZSP

WBB4	Model:	WBB4
Q	LED Mfr:	Q=QSSI
F	Optics:	F=Medium Beam Spread
1X	Number of Arrays:	1X=One
16	Wattage:	16=16w
U	Ballast:	U=120-277V
4K	CCT:	4K=4000K
C	Lens:	C=Clear Array Lens
Z	Color:	Z=Bronze, B=Black
SP	Options:	SF=Single Fuse, DF=Double Fuse, SP=Surge Protection

KELSEY-KANE LIGHTING MFG. CO.

Voice & Text: 954-772-3187

E-Mail: info@kelsey-kane.com

Website: www.kelsey-kane.com