




WPR40GRQ

EasyLED Acclaim Wall Pack Grid Frame



Dimensions

Diameter (D)	15" (380mm)
Height (A)	9 1/4" (235mm)

The Round Acclaim Wall pack is designed to replace HID lighting systems up to 175w MH or HPS. The grid frame helps protect the borosilicate glass lens and adds a decorative appearance. Typical applications include office and public buildings, condominiums, schools, shopping malls, and hospitality. Recommended mounting heights are 8 to 20 feet.

Specifications and Features:

Housing:

15" Diameter Die Cast Aluminum Housing & Grid Top Frame, 1/2" Coin Plugs with O-rings for Conduit & Photocell.

Listing & Ratings:

CSA: Listed for Wet Locations, ANSI/UL 1598, 8750; IP65 Sealed LED Compartment.

Finish:

Textured Powdercoat Finish Over a Chromate Conversion Coating. Custom Colors Available Upon Request.

Lens:

Clear Prismatic Molded Borosilicate Glass Lens

Mounting Options:

Cast-in Template for Mounting Directly Over a 4" Recessed Outlet Box, or Use 1/2" Surface Conduit.

EasyLED LED:

Aluminum Boards

Wattage:

Array: 22.7w, System: 27.2w; (175w HID Equivalent)

Driver:

Electronic Driver, 120-277V, 50/60Hz or 347-480V, 50/60Hz; Less Than 20% THD and PF>0.90. Standard Internal Surge Protection 2kV. 0-10V Dimming Standard for a Dimming Range of 100% to 10%; Dimming Source Current is 150 Microamps.

Warranty:

5-Year Warranty for -40°C to +40°C Environment.

Order Information Example:

WPR40GRQF1X23U5KCZSP

WPR40GRQ	F	1X23		5K	C		
Model	Optics	Wattage	Driver	CCT	Lens	Color	Options
AIWPR40GRQ=EasyLED Acclaim Wall Pack Grid Frame	F=Type IV	1X23=23w	U=120-277V H=347-480V	5K=5000K	C=Clear	Z=Bronze W=White C=Custom (Consult Factory)	SF=Single Fuse (120-277V Only) DF=Double Fuse (120-277V Only) SP=Surge Protector BU=Battery Backup, 90 Minutes

Project Information:

Project Name: _____ Fixture Type: _____

Complete Catalog #: _____ Date: _____

Comments: _____

Certification & Listings:






KELSEY-KANE LIGHTING MANUFACTURING COMPANY

"Serving Lighting Professionals Since 1978"

WPR40GRQ

EasyLED Acclaim Wall Pack Grid Frame

Accessories & Replacement Parts:



WPR40GLC



WPR40TRBZ

Replacement Parts (Order Separately, Field Installed)

WPR40GLC Clear Prismatic Molded Borosilicate Glass Lens

WPR40TRBZ Trim Ring, Die Cast Aluminum, 19½" Outer Diameter, Allows Recessed Mounting of Fixture, Textured Bronze Powdercoat Finish

For Replacement Battery Backup, see the LEPC LED Battery Backup Specification Sheet.